Specifications

Application	Final Filtration for Particulates in Soft Drinks, Particle Reduction in Bottle Water Manufacturing, Particle Reduction in Distilled Spirits Filtration, RO Protection and Prefiltration, Solids Removal, Solids Removal, Recovery & Reclaim, Turbidity and Particle Control in Soft Drink Water, Water Filtration for Beer Applications, Water Filtration for Wine Applications
Brand	Betafine™
End Configuration	226 O-Ring and Spear
End Modification	226 O-Ring and Spear, Sanitary Fitting
Factory Integrity Tested	Yes
Filter Material	Graded Density Polypropylene
Filter Technology	Non-Woven
Filter Type	Surface
Gasket/O-ring Material	Silicone
Industries	Life Sciences
Maximum Operating Temperature (Celsius)	80 Degree Celsius
Maximum Operating Temperature (Fahrenheit)	175 Degree Fahrenheit
Micron Rating	0.2 μm ABS, 1.2 μm ABS
Overall Length (Imperial)	20 in, 30 in
Overall Length (Metric)	50.8 cm, 76.2 cm
Overall Width (Imperial)	3 in
Overall Width	7.62 cm

(Metric)		
Product Type	Cartridge, Filter Capsule	
Series	Betafine™ PTG Series	