

## Specifications

<b>Application</b>	<b>Sterilizing Grade Filtration, Sterilizing Grade Filtration (liquid and gas)</b>
<b>Brand</b>	<b>LifeASSURE™</b>
<b>Component and Assembly Materials</b>	<b>Polypropylene, Reinforcing Ring: Stainless Steel</b>
<b>End Configuration</b>	<b>222 O-Ring and Flat Cap, 222 O-Ring and Spear, 226 O-Ring and Flat Cap, 226 O-Ring and Spear</b>
<b>End Modification</b>	<b>222 O-ring &amp; Flat Cap, 222 O-ring &amp; Spear, 226 O-ring &amp; Flat Cap, 226 O-ring &amp; Spear</b>
<b>Filter Material</b>	<b>PTFE</b>
<b>Filter Technology</b>	<b>Membrane</b>
<b>Filter Type</b>	<b>Surface</b>
<b>Formulation</b>	<b>Pharmaceutical, Sterile Air, Vent Filtration</b>
<b>Gasket/O-ring Material</b>	<b>EPR, Fluorocarbon, PTFE Encapsulated Fluorocarbon, Silicone</b>
<b>Grade</b>	<b>Sterilizing Grade</b>
<b>Industries</b>	<b>Life Sciences</b>
<b>Maximum Operating Temperature (Celsius)</b>	<b>40 Degree Celsius, 80 Degree Celsius</b>
<b>Maximum Operating Temperature (Fahrenheit)</b>	<b>176 Degree Fahrenheit</b>
<b>Micron Rating</b>	<b>0.2 Absolute, @ 95%, 0.2 µm</b>
<b>Overall Length (Imperial)</b>	<b>10 in, 2.5 in, 20 in, 30 in, 5 in</b>
<b>Overall Length (Metric)</b>	<b>12.7 cm, 25.4 cm, 50.8 cm, 6.35 cm, 76.2 cm</b>
<b>Product Type</b>	<b>Cartridge, Pleated Membrane</b>
<b>Series</b>	<b>LifeASSURE™ PFS Series</b>