

## Specifications

<b>Application</b>	<b>Amine Sweetening, Completion &amp; Workover Fluids, Final Filtration for Particulates in Soft Drinks, Hydrotreater Feed, Membrane System Protection, Particle Reduction in Bottle Water Manufacturing, Particle Reduction in Distilled Spirits Filtration, Process Cooling Water, RO Protection and Prefiltration, Turbidity and Particle Control in Soft Drink Water, Water Filtration for Beer Applications, Water Filtration for Wine Applications, Water Injection for Enhanced Oil Recovery</b>
<b>Brand</b>	<b>Micro-Klean™</b>
<b>End Modification</b>	<b>None</b>
<b>Filter Material</b>	<b>Bleached Cotton, Polypropylene</b>
<b>Filter Technology</b>	<b>Non-Woven</b>
<b>Filter Type</b>	<b>Depth</b>
<b>Flow Rate (Imperial)</b>	<b>4 GPM, 5 GPM, 6 GPM</b>
<b>Flow Rate (Metric)</b>	<b>15.1 Litre per minute, 18.9 Litre per minute, 22.7 Litre per minute</b>
<b>Grade</b>	<b>C, F, L, V, W, White, Y</b>
<b>Industries</b>	<b>Industrial</b>
<b>Maximum Operating Temperature (Celsius)</b>	<b>121 Degree Celsius, 60 Degree Celsius</b>
<b>Maximum Operating Temperature (Fahrenheit)</b>	<b>140 Degree Fahrenheit, 250 Degree Fahrenheit</b>
<b>Micron Rating</b>	<b>1 Absolute, @ 95%, 10 Absolute, @ 95%, 10 µm, 100 Absolute, @ 95%, 25 Absolute, @ 95%, 3 Absolute, @ 95%, 350 Absolute, @ 95%, 5 Absolute, @ 95%, 50 Absolute, @ 95%, 75 Absolute, @ 95%</b>
<b>Overall Length (Imperial)</b>	<b>19.5 in, 20 in, 29.25 in, 30 in, 40 in, 9.875 in</b>
<b>Overall Length (Metric)</b>	<b>101.6 cm, 25.083 cm, 49.53 cm, 50.8 cm, 74.3 cm, 76.2 cm</b>
<b>Product Type</b>	<b>Cartridge</b>
<b>Series</b>	<b>Micro-Klean™ CS Series</b>